SUPERFLOATS BERTHING PONTOON (SBP)



Superfloats Berthing Pontoon (SBP)

Superfloats Berthing Pontoons (SBP) are particularly practical. The flotation units consist of Superfloats Concrete Floats (SCF) or PE floats units. It is at times both types of floats are used in combination for stability & buoyancy reasons.

The Superfloats Berthing Pontoon (SBP) are suitable in various applications of higher tidal range sites to shorten gangway length for easy maintenance reasons.







Features:

- If required, can be equipped with lifting davit for Superfloats Self Levelling Gangway (SSLGW) purpose.
- ➤ Marine grade aluminium construction.
- A few options available i.e. customdesigned railing, adjustable chain stops ranges, and pull-up rope types.
- Can be custom designed to meet various applications.

Advantages :

Superfloats Berthing Pontoon (SBP) offers an alternative method of waterfront access which is practical & convenient to use.

- ✓ It can meet stringent slope/gradient specification called for in most maritime codes.
- ✓ It can also incorporate an added selfleveling stairs or gangway thereby allow greater height differential wrt the length of gangway, if required.
- $\boxed{\checkmark}$ It is self-adjusting to tidal changes.
- ✓ It can be designed fixed or as movable unit. Movable unit can be transferred to different location, if required.

* Product details and specifications are subject to change without notice.



No. 16, Jalan Korporat 5/KU9, Off Persiaran Hamzah Alang, Taman Perindustrian Meru, 42200 Klang, Selangor, Malaysia.

Phone: +603-3393 3622 Website: www.superfloats.com <u>Email: superflo</u>atsmalaysia@gmail.com Fax: +603-3393 3772